

Schedule V
[See rule 3 (ze) and (zf)]
PART A

Specifications of used oil suitable for reprocessing / recycling

<u>S. No.</u>	<u>Parameter</u>	<u>Maximum permissible Limits</u>
<u>(1)</u>	<u>(2)</u>	<u>(3)</u>
1.	<u>Polychlorinated biphenyls (PCBs)</u>	<u><2 ppm *</u>
2.	<u>Lead</u>	<u>100 ppm</u>
3.	<u>Arsenic</u>	<u>5 ppm</u>
4.	<u>Cadmium+Chromium+Nickel</u>	<u>500 ppm</u>
5	<u>Polyaromatic hydrocarbons (PAH)</u>	<u>6%</u>

PART B

Specifications of fuel derived from Waste Oil

S. No.	Parameter	Maximum permissible Limits
(1)	(2)	(3)
1.	Sediment	0.25 %
2.	Lead	100 ppm
3.	Arsenic	5 ppm
4.	Cadmium+Chromium+Nickel	500 ppm
5.	Polyaromatic hydrocarbons (PAH)	6%
6.	Total halogens	4000 ppm
7.	Polychlorinated biphenyls (PCBs)	<2 ppm *
8.	Sulfur	4.5 %
9.	Water Content	1 %

* **The detection limit is 2 ppm by Gas Liquid Chromatography (GLC) using Electron Capture detector (ECD)**